




55BA-AS
llaves fijas de dos bocas abiertas antichispa

• Medidas en pulgadas



	art.		A mm	A1 mm	L mm	S mm	 g
000550853	55BA-AS	3/8x7/16	23	26	110	6,3	60
000550854	55BA-AS	1/2x9/16	29	31	130	7,1	90
000550857	55BA-AS	5/8x11/16	35	38	160	7,9	155
000550859	55BA-AS	3/4x13/16	41	44	180	9,0	225
000550865	55BA-AS	7/8x15/16	46	49	210	10,2	305
000550868	55BA-AS	1x1.1/16	51	55	230	11,4	405
000550870	55BA-AS	1.1/8x1.3/16	59	61	245	13,7	548
000550872	55BA-AS	1.1/4x1.5/16	65	67	255	15,4	600



Strobiliato e marcato in base beta-ottone (beta-cu) e non deve essere usato in contatto con prodotti a base di acqua ossigenata (pericoloso per l'ambiente).

Il prodotto può reagire con l'ossigeno dell'aria e formare ossidi e altri prodotti.

Este instrumento debe ser usado en contacto con agua oxigenada (peligroso para el medio ambiente).

Aluminum tool used with the copper alloy tool surface may produce sparks and any dangerous explosion.